

**Heat Wrap (3 cells)**

29 x 9 cm

**WRAP**

Data	Unit	Value	Tolerance
Material	-	Woven non woven	-
Composition	-	Interlaced polyethylene (LDPE) and polypropylene (PP) fibre	-
Grammage	g/m <sup>2</sup>	105	±10 %
Thickness	mm	0,28	±10 %
Dimensions (folded)	cm	9,5x9,0	±10 %
Dimensions (extended)	cm	28,7 x 8,9	±10 %
Total weight	g	43,1	±10 %
Activation method	-	Contact with Air	-
Warm-up Time	minutes	15	Max
Heat wrap	hours	≥ 12	-
Mean Temperature	°C	42	+/-2°C


**ACTIVE COMPONENTS**

Data	Unit	Value	Tolerance
Components:	-	-	-
Iron Powder	%	60%	±10 %
Vermiculite	%	20%	±10 %
Activated Carbon	%	10%	±10 %
Sodium Chloride	%	6%	±10 %
Water	%	4%	±10 %



**ADHESIVE**

Data	Unit	Value	Tolerance
Grammage	g/m <sup>2</sup>	60	±10 %
Composition:	-	-	-
Butyl Acrylate	%	14	-
Acroleic Acid	%	5	-
EHA (2-Ethylhexyl Acrylate)	%	26	-
Acetic Ether	%	50	-
Jaffaite	%	5	-


**SILICON PAPER**

Data	Unit	Value	Tolerance
Type	-	One sided silicon paper	-
Grammage	g/m <sup>2</sup>	60	±10 %
Recycling code	-		-









**PRIMARY PACKAGING**

Data	Unit	Value	Tolerance
Type	-	Hot sealed envelope	-
Material	-	Polyestere/Aluminium/Polythene	-
Grammage	g/m <sup>2</sup>	115 g/m <sup>2</sup>	± 5%
Symbols	-		-
Recycling code	-		-

**SECONDARY PACKAGING**

Data	Unit	Value	Tolerance
Type	-	Case	-
Material	-	Cardboard	-
Grammage	g/m <sup>2</sup>	240	±10%
Recycling code	-		-

**MANDATORY WORDINGS**

Data	Symbols	Definition
Manufacturer address		EUROSIREL S.p.A. - viale Europa, 30 - 20047 Cusago (MI) - Italy
CE mark		CE conformity mark
Batch		YSSNNNN
Expiry date		YYYY-MM
Product shelf life	-	5 years
Conservation method		Keep in a cool and dry place, keep away from sunlight
Classification		Medical Device
Using		Monouse
REF code		CRXXXXXX
UDI-DI (Base) code	-	8017990CRUP