

PAC®

The only REACH registered and USDA certificated 100% bio-based PCM available on the market

CONSTANT **TEMPERATURE COOLING PACKS**





When the ambient

temperature rises,

the PCM starts to melt.

Solid PCM

When the PCM starts

has been released.

to recrystallize, it releases

the stored latent heat, while maintaining a constant tem-

perature, until all latent heat

INSERTS INTO GARMENTS POCKET



FNJOY CONSTANT COOLING

For when exact temperatures matter.

29°C / 84°F

24°C / 75°F

21°C / 70°F

15°C / 59°F

6.5°C / 44°F

During the phase transition.

liquid PCM

the PCM stores energy as

latent heat, maintaining a constant temperature until

the cooling product is

completely melted.

Our renewable bio-based Phase Change Material (PCM) cooling technology, is produced with materials of vegetable origin. Our INUTEQ PAC® products out-perform paraffin and salt hydrates PCM in a number of areas:

- Improved fire safety .
- Long term stability
- High latent heat capacities
- Safer handling
- Sourced from recyclable materials

Available in 5 different temperatures:

- 6.5°C / 44°F Art. nr.: 1364020608 (Sport)
- 15°C / 59°F Art. nr.: 1364021508 (Sport)
- 21°C / 70°F Art. nr.: 1364022108 (Work)
- 24°C / 75°F Art. nr.: 1364022408 (Work)
- 29°C / 84°F Art. nr.: 1364022908 (Work)

Our bio-based PCM is non-toxic, 100% biodegradable, low-flammable, durable, reusable, 20% lighter than water, and do not produce condensation.

Activation: Simply put the product in ice water, refrigerator or freezer of store it at a lower temperature until it becomes fully solid.

Cooling duration:	1 up to 4.5 hours = depending
	selected PCM temperature.
Weight:	Approx. 0,35kg per insert (4 total)
Sizes one element:	One pack = 15 cm x 31,4 cm
	5,9 inch x 12,36 inch
Components:	
Foil:	INUTEQ-SEAL®

*Please order the bio-based PCM inserts (set of 4 units) separately.



Osnabrückstraat 30 7418 BN Deventer The Netherlands

INUTEQ INTERNATIONAL B.V. For more info or any questions, please contact us at: Tel. +31 (0) 85 065 3797 E-mail: support@inuteq.com



When the ambient

recrystallize.

temperature lowers. the PCM starts to

WWW.INUTEQ.COM

PACKS